according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878

Z] ZOBEL Coating Systems

ZZ89-0000-0AA [Z] DecoTec® 5446

Revision date 20 Jun 2025 Print date 20 Jun 2025 Version 12.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Trade name/designation

ZZ89-0000-0AA [Z] DecoTec® 5446

TopOil 2in1 UVPlusX

0000 colorless

UFI: MMER-M051-1002-0STY

1.2 Relevant identified uses of the substance or mixture and uses advised against

paint and/or paint-related material

Relevant identified uses

Reserved for industrial and professional use.

1.3 Details of the supplier of the safety data sheet

Supplier

Berger-Zobel GmbH **Coating Systems**

Maybachstr. 2 Telephone: +49 6359 8005-0 67269 Grünstadt E-mail: info@berger-zobel.de Website: www.berger-zobel.de Germany

Department responsible for information

E-mail (competent person) Sicherheitsdaten@berger-zobel.de

1.4 Emergency telephone number

Emergency telephone number +49 700 24112112

24 hr. emergency phone number

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



GHS07

Signal word

Warning

Hazard statements

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Wear protective gloves and eye protection/face protection.

Hazard components for labelling

Hydroxyphenyl-benzotriazole derivatives

Phthalic anhydride

Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate

Supplemental hazard information

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Page 1/10 GB (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA [Z] DecoTec® 5446

Version 12.0 Revision date 20 Jun 2025 Print date 20 Jun 2025

Spontaneous ignition possible through autoxidation of cloths soaked in the product.

Also dusts and other soaked objects. The product itself is not self-igniting.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

SECTION 3: Composition/information on ingredients.

3.2 Mixtures

Description

Öle/Wachse, lösemittelreich, entaromatisiert

Hazardous ingredients

CAS No. EC No. Index No.	Substance name REACH No. Classification according to Regulation (EC) No 1272/2008 [CLP]	weight-%
- 918-481-9 649-327-00-6	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics 01-2119457273-39-XXXX Asp. Tox. 1 H304 / EUH066	35,0 < 50,0
- 918-167-1 -	Kohlenwasserstoffe, C11-C12, Iso-Alkane, <2% Aromaten 01-2119472146-39-XXXX Flam. Liq. 3 H226 / Asp. Tox. 1 H304	8,00 < 10,0
1065336-91-5 915-687-0	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate 01-2119491304-40-XXXX Skin Sens. 1A H317 / Repr. 2 H361 / Aquatic Acute 1 H400 / Aquatic Chronic 1 H410	1,00 < 2,00
34590-94-8 252-104-2	(2-methoxymethylethoxy)propanol 01-2119450011-60-XXXX Substance with a common (EC) occupational exposure limit value.	1,00 < 2,00
64742-47-8 265-149-8 649-422-00-2	Distillates (petroleum), hydrotreated light 01-2119484819-18-XXXX Asp. Tox. 1 H304	1,00 < 2,00
- 400-830-7 607-176-00-3	Hydroxyphenyl-benzotriazole derivatives 01-0000015075-76-XXXX Skin Sens. 1 H317 / Aquatic Chronic 2 H411	0,500 < 1,00
85-44-9 201-607-5 607-009-00-4	Phthalic anhydride 01-2119457017-41-XXXX Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Skin Sens. 1 H317 / Eye Dam. 1 H318 / Resp. Sens. 1 H334 / STOT SE 3 H335	0,150 < 0,200

Remark

Full text of H- and EUH-statements: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

Following inhalation

In case of irregular breathing or respiratory arrest provide artificial respiration. Remove casualty to fresh air and keep warm and at rest.

Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

Page 2/10 GB (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA

[Z] DecoTec® 5446

Version 12.0 Revision date 20 Jun 2025

Print date 20 Jun 2025

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3 Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

alcohol resistant foam, Carbon dioxide (CO2), Powder, spray mist, (water)

Unsuitable extinguishing media

Strong water jet

5.2 Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3 Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

For containment

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

For cleaning up

Clean using cleansing agents. Do not use solvents.

6.4 Reference to other sections

Safe handling: see section 7

Personal protection equipment: refer to section 8

Disposal: see section 13

SECTION 7: Handling and storage

'.1 Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Personal protection equipment: see section 8. Do not empty containers with pressure no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Advices on general occupational hygiene

When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Page 3/10 GB (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA

[Z] DecoTec® 5446

Version 12.0 Revision date 20 Jun 2025

Print date 20 Jun 2025

Storage class

LGK10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions

Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Store in a well-ventilated and dry room at temperatures between $5\,^{\circ}\text{C}$ and $25\,^{\circ}\text{C}$.

7.3 Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

CAS No.	Substance name	Source	Long-term /short-term (Spitzenbegrenzung)
34590-94-8	(2-methoxymethylethoxy)propanol	WEL	308 / - (-) mg/m³ (may be absorbed through the skin)
64742-47-8	Distillates (petroleum), hydrotreated light	WEL	800 / - (-) mg/m ³ (> or = C7, Cycloalkanes)
64742-47-8	Distillates (petroleum), hydrotreated light	WEL	1,200 / - (-) mg/m ³ (alkanes >= C7)
85-44-9	Phthalic anhydride	WEL	4 / 12 (-) mg/m³
64-17-5	ethanol; ethyl alcohol	WEL	1,920 / - (-) mg/m ³

Additional information

Long-term: Long-term occupational exposure limit value short-term: short-term occupational exposure limit value

Biological limit values

No data available

DNEL worker

CAS No.	Substance name	DNEL type	DNEL value
34590-94-8	(2-methoxymethylethoxy)propanol	Long-term – inhalation, systemic effects	308 mg/m³
34590-94-8	(2-methoxymethylethoxy)propanol	Long-term - dermal, systemic effects	283 mg/kg bw/day
-	Hydroxyphenyl-benzotriazole derivatives	DNEL long-term dermal (systemic)	0.25 mg/kg
-	Hydroxyphenyl-benzotriazole derivatives	DNEL long-term inhalative (systemic)	0.35 mg/m³
85-44-9	Phthalic anhydride	Long-term – inhalation, systemic effects	49.4 mg/m³
85-44-9	Phthalic anhydride	Long-term - dermal, systemic effects	14 mg/kg bw/day
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	Long-term – inhalation, systemic effects	1.27 mg/m³
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	Long-term - dermal, systemic effects	1.8 mg/kg bw/day

DNEL Consumer

CAS No.	Substance name	DNEL type	DNEL value
34590-94-8	(2-methoxymethylethoxy)propanol	Long-term – inhalation, systemic effects	37.2 mg/m³
34590-94-8	(2-methoxymethylethoxy)propanol	Long-term - dermal, systemic effects	121 mg/kg bw/day
34590-94-8	(2-methoxymethylethoxy)propanol	Long-term - oral, systemic effects	36 mg/kg bw/day

Page 4/10 GB (en_GB)

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA [Z] DecoTec® 5446 Version 12.0 Revision date 20 Jun 2025

Print date 20 Jun 2025

		-	
-	Hydroxyphenyl-benzotriazole derivatives	DNEL long-term dermal (systemic)	0.025 mg/kg
-	Hydroxyphenyl-benzotriazole derivatives	DNEL long-term inhalative (systemic)	0.085 mg/m³
85-44-9	Phthalic anhydride	Long-term – inhalation, systemic effects	8.7 mg/m³
85-44-9	Phthalic anhydride	Long-term - dermal, systemic effects	5 mg/kg bw/day
85-44-9	Phthalic anhydride	Long-term - oral, systemic effects	5 mg/kg bw/day
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	Long-term – inhalation, systemic effects	0.31 mg/m³
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	Long-term - dermal, systemic effects	0.9 mg/kg bw/day
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	Long-term - oral, systemic effects	0.18 mg/kg bw/day

PNEC

CAS No.	Substance name	PNEC type	PNEC Value
34590-94-8	(2-methoxymethylethoxy)propanol	aquatic, intermittent release	190 mg/L
34590-94-8	(2-methoxymethylethoxy)propanol	aquatic, marine water	1.9 mg/L
34590-94-8	(2-methoxymethylethoxy)propanol	sewage treatment plant	4,168 mg/L
34590-94-8	(2-methoxymethylethoxy)propanol	sediment, freshwater	70.2 mg/kg sediment dw
34590-94-8	(2-methoxymethylethoxy)propanol	sediment, marine water	7.02 mg/kg sediment dw
	Hydroxyphenyl-benzotriazole derivatives	PNEC aquatic, freshwater	μg/L
-	Hydroxyphenyl-benzotriazole derivatives	PNEC aquatic, intermittent release	μg/L
	Hydroxyphenyl-benzotriazole derivatives	PNEC aquatic, marine water	ng/L
-	Hydroxyphenyl-benzotriazole derivatives	PNEC sewage treatment plant (STP)	mg/L
	Hydroxyphenyl-benzotriazole derivatives	PNEC sediment, freshwater	mg/kg sediment dw
	Hydroxyphenyl-benzotriazole derivatives	PNEC sediment, marine water	μg/kg sediment dw
	Hydroxyphenyl-benzotriazole derivatives	PNEC soil	mg/kg dry weight
85-44-9	Phthalic anhydride	aquatic, intermittent release	5.6 mg/L
85-44-9	Phthalic anhydride	aquatic, marine water	0.1 mg/L
85-44-9	Phthalic anhydride	sewage treatment plant	10 mg/L
85-44-9	Phthalic anhydride	sediment, freshwater	3.8 mg/kg sediment dw
85-44-9	Phthalic anhydride	sediment, marine water	0.38 mg/kg sediment dw
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	aquatic, intermittent release	0.009 mg/L
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	aquatic, marine water	0 mg/L
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	sewage treatment plant	1 mg/L
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	sediment, freshwater	1.05 mg/kg sediment dw
1065336-91-5	Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate	sediment, marine water	0.11 mg/kg sediment dw

8.2 Exposure controls

Page 5/10 GB (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA [Z] DecoTec® 5446

Version 12.0 Revision date 20 Jun 2025 Print date 20 Jun 2025

Provide good ventilation. This can be achieved with local or room suction.

Personal protection equipment

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Hand protection

Suitable material: NBR (Nitrile rubber)
Thickness of the glove material >= 0.4 mm

Breakthrough time >= 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles: EN ISO 374

Skin protection

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Eye glasses with side protection: EN 166

Body protection

When handling with chemical substances, protective clothing with CE-labels including the four control digits must be worn. Antistatic clothing including shoes are recommended.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Liquid
Colour brown

Odour characteristic
pH at 20 °C not applicable
Melting point/freezing point not determined

Initial boiling point and boiling range 125 °C

Source: Distillates (petroleum), hydrotreated light

Flash point > 61 °C

flammability not applicable
Lower explosion limit at 20°C 0.6 Vol-%

Source: Distillates (petroleum), hydrotreated light

Upper explosion limit at 20°C 14 Vol-%

Source: (2-methoxymethylethoxy)propanol

Vapour pressure at 20°C 0.843 mbar
Relative vapour density not applicable
Density at 20 °C 0.88 kg/l

Water solubility at 20°C practically insoluble
Partition coefficient: n-octanol/water see section 12

Ignition temperature in °C > 200 °C

Source: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Decomposition temperature not determined

Viscosity at 20 °C 80 mm²/s

particle characteristics not applicable

9.2 Other information

Solid content 45.7 %

Page 6/10 GB (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA [Z] DecoTec® 5446

Version 12.0 Revision date 20 Jun 2025 Print date 20 Jun 2025

solvent content 54.3 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3 Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4 Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5 Incompatible materials

No further relevant information available.

10.6 Hazardous decomposition products

Decomposition products in case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

Overall assessment on CMR properties

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: Headache, Dizziness, fatigue, amyosthenia, Dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

11.2 Information on other hazards

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Acute (short-term) toxicity to aquatic invertebrates

Page 7/10 GB (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA

[Z] DecoTec® 5446

Version 12.0 Revision date 20 Jun 2025

Print date 20 Jun 2025

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LC50: > 0.002 mg/L (96 h)

Chronic (long-term) fish toxicity

(Oncorhynchus mykiss (Rainbow trout)):

Chronic (long-term) toxicity to aquatic invertebrate

NOELR: 1 mg/L (21 d)

Toxicity to microorganisms

2 (5 h

12.2 Persistence and degradability

(2-methoxymethylethoxy)propanol

Biodegradation = 75 % (28 d)

Biodegradation = 93 % (13 d)

12.3 Bioaccumulative potential

(2-methoxymethylethoxy)propanol

Partition coefficient: n-octanol/water = 1.01

Partition coefficient: n-octanol/water >= 3.17 (Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics)

* Phthalic anhydride

Partition coefficient: n-octanol/water = 1.6

Partition coefficient: n-octanol/water = 0.35 ((2-methoxymethylethoxy)propanol)

* Partition coefficient: n-octanol/water = 1.43 (Phthalic anhydride)

Partition coefficient: n-octanol/water > 1.52 (Reaction mass of bis(1,2,2,6,6-pentamethylpiperidin-4-yl) sebacate and methyl 1,2,2,6,6-pentamethylpiperidin-4-yl sebacate)

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Do not empty into drains; dispose of this material and its container in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

Waste codes/waste designations according to EWC/AVV

080111* - Waste paint and varnish containing organic solvents or other dangerous substances

* Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Other disposal recommendations

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1 UN number or ID number

not applicable

14.2 UN proper shipping name

Land transport (ADR/RID)

No dangerous good in sense of these transport regulations.

Sea transport (IMDG)

No dangerous good in sense of these transport regulations.

Page 8/10 GB (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA

[Z] DecoTec® 5446

Version 12.0 Revision date 20 Jun 2025 Print date 20 Jun 2025

Air transport (ICAO-TI / IATA-DGR)

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

not applicable

14.4 Packing group

not applicable

14.5 Environmental hazards

Land transport (ADR/RID) not applicable Sea transport (IMDG) not applicable

14.6 Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

14.7 Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

14.8 Additional information

Land transport (ADR/RID)

not applicable

Sea transport (IMDG)

not applicable

Air transport (ICAO-TI / IATA-DGR)

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Regulation (EC) No. 1907/2006 (REACH), Annex XVII (restrictions)

Use restriction according to REACH annex XVII, no.: 03, 40

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive 92/85/EEC or stricter national regulations, if applicable. Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC) or stricter national regulations, if applicable.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC value: 459 g/l

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds

VOC limit value: 2004/42/IIA(i): 500 g/l (2010)

Maximum VOC content of the product in a ready to use condition: 476 g/L. This product meets the requirements of Regulation (EC) No. 1935/2004 on the limitation of VOC content.

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] Hazard categories / Named dangerous substances

This product is not classified according to Directive 2012/18/EU.

National regulations

Observe in addition any national regulations!

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

List of relevant hazard statements and/or precautionary statements from sections 2 to 15

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

Page 9/10 GB (en_GB)

according to Regulation (EC) No. 1907/2006 (REACH) according to Regulation (EU) 2020/878



ZZ89-0000-0AA	[Z] DecoTec® 5446	
Version 12.0	Revision date 20 Jun 2025	Print date 20 Jun 2025
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H335	May cause respiratory irritation.	
H361	Suspected of damaging fertility or the unborn child (state specific effect if if it is conclusively proven that no other routes of exposure cause the haza	
H400	Very toxic to aquatic life.	,
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	
EUH066	Repeated exposure may cause skin dryness or cracking.	

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Sens. 1 Calculation method.
Aquatic Chronic 3 Calculation method. **Key literature references and sources for data**

Data arise from reference works and literature.

Abbreviations and acronyms

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

OEL: Occupational Exposure Limit Value

BLV: Biological limit values CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging CMR: Carcinogenic, Mutagenic and Reprotoxic

DIN: German Institute for Standardization / German industrial standard

DNEL: Derived No-Effect Level

EAKV: European Waste Catalogue Directive

EC: Effective Concentration EC: European Community EN: European Standard

EU/EEA: European Economic Area

IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

IBC Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

ICAO-TI: International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG Code: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

LC: Lethal Concentration

LD: Lethal Dose

MARPOL: Maritime Pollution: The International Convention for the Prevention of Pollution from Ships

OECD: Organisation for Economic Cooperation and Development

PBT: persistent, bioaccumulative, toxic PNEC: Predicted No Effect Concentration

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

UN: United Nations

VOC: Volatile Organic Compounds

vPvB: very persistent and very bioaccumulative

Indication of changes

* Data changed compared with the previous version.

Page 10/10 GB (en_GB)