Article Print d Versio	ate: 25.04.20	23 Ŕ	Z] DecoTec® 5410 Revision date: 17.03 ssue date: 17.03.20	3.2023	El Page 1 /	
SEC	TION 1: Identification	on of the su	ubstance/mixtur	re and of the company	/undertak	ing
1.1.	Product identifier					
	Article No. (manufactu Trade name/designat)	XP82000AAJ10 [Z] DecoTec® 5410 Dip glaze Basis DEL		
1.2.	Relevant identified u	ises of the s	substance or mixt	ture and uses advised ag	jainst	
	Relevant identified u paint and/or paint rela Reserved for industria	ted material				
1.3.	Details of the suppli	er of the saf	fety data sheet			
	supplier (manufactu Berger-Zobel GmbH Coating Systems Maybachstraße 2 67269 Grünstadt	rer/importer	r/downstream use	er/distributor) Telephone: +49 6359 / 80 Telefax: +49 6359 / 8005-		
	Department respons Laboratory E-mail	ible for info	ormation:	Sicherheitsdaten@berger	r-zobel de	
1.4.	Emergency telephor 24-hour emergency n (BLG)	umber: +49 7		38271 or +11 49 700 24112		
SEC	TION 2: Hazards ide	entification	1			
2.1.	Classification of the	substance	or mixture			
	Classification accor	ding to Reg	ulation (EC) No 12	272/2008 [CLP]		
	The mixture is classifi	ed as not ha	zardous according	to regulation (EC) No 127	2/2008 [CL	P].
2.2.	Label elements Labelling according Hazard pictograms	to Regulation	on (EC) No. 1272/	2008 [CLP]		
	Hazard statements	not applical	ble			
	Precautionary stater	nents not applical	ble			
	Hazard components	for labelling not applical	-			
	Supplemental hazar EUH208			(2H)-one; 2-methylisothiaz	zol-3(2H)-or	ne. May produce an allergic
	EUH210	Safety data	sheet available or	n request.		
2.3.	Other hazards					
	No information availa	ble.				
	Other information: If children. Read label			ave product container or	label at ha	nd. Keep out of reach of
SEC	TION 3: Compositio	on/informat	tion on ingredie	nts		
3.2.	Mixtures					
	Description					
			ulation (EC) No 4			

[Z] ZOBEL

Classification according to Regulation (EC) No 1272/2008 [CLP] EC No. REACH No. CAS No.

Article Print o Versio	date:	XP82000AAJ10[Z] DecoTec® 541025.04.2023Revision date: 17.03.20234.0003Issue date: 17.03.2023		EN Coating System	
	Index No.	Design classif	ation ication // Remark	N N	weight-%
		not app	licable		
	Full text of TION 4: Fi	information classification: see s rst aid measures			
4.1.		n of first aid meas	ures		
	General in	formation			
			n symptoms persist, seek medical adv seek medical advice.	vice. In case of unconsciousness give not	thing by mouth,
	In case of Remove ca respiration	asualty to fresh air	and keep warm and at rest. In case c	f irregular breathing or respiratory arrest	provide artificial
	Take off im	skin contact mediately all conta vents or thinners.	minated clothing. After contact with s	kin, wash immediately with plenty of wate	er and soap. Do
	A 64				

Z ZOBEL

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

Following ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. **Indication of any immediate medical attention and special treatment needed** First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

Article No.:	XP82000AAJ10	[Z] DecoTec® 5410
Print date:	25.04.2023	Revision date: 17.03.2023
Version:	4.0003	Issue date: 17.03.2023

Coating Systems

Z ZOBEL

Page 3/7

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear closely fitting protective glasses in case of splashes.

Body protection

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.



Article No.:	XP82000AAJ10	[Z] DecoTec® 5410	
Print date:	25.04.2023	Revision date: 17.03.2023	
Version:	4.0003	Issue date: 17.03.2023	

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

	Physical state:	Liquid
	Colour:	refer to chapter 1.
	Odour:	characteristic
	Odour threshold:	not applicable
	Melting point/freezing point:	not applicable
	Initial boiling point and boiling range:	100 °C
		Source: Water
	Flammability:	not applicable
	Lower and upper explosion limit:	
	Lower explosion limit:	2,6 Vol-%
	Upper explosion limit:	12,6 Vol-% Source: Propane-1,2-diol
	Flash point:	not applicable
	Auto-ignition temperature:	410 °C
		Source: Propane-1,2-diol
	Decomposition temperature:	not applicable
	nH at 20 °C.	not applicable
	pH at 20 °C:	not applicable < 80 mm²/s
	Cinematic viscosity (40°C):	< 80 mm ⁻ /S
	Viscosity at 20 °C:	15 s 4 mm
		Method: DIN 53211
	Solubility(ies):	
	Water solubility at 20 °C:	partially soluble
	Partition coefficient: n-octanol/water:	see section 12
	Vapour pressure at 20 °C:	23 mbar
		Method: calculated. Source: Water
	Density and/or relative density:	Source. Water
	Density at 20 °C:	1,03 g/cm³
		Method: ISO 2811, part 3
	Relative vapour density:	not applicable
	particle characteristics:	not applicable
9.2.	Other information	
	Solid content:	23,72 weight-%
	solvent content:	
	Organic solvents:	4 weight-%
	Water:	72 weight-%
	Solvent separation test:	< 3 weight-% (ADR/RID)
	FION 10: Stability and repativity	

SECTION 10: Stability and reactivity

10.1. Reactivity

9

No information available.

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.



Article No.:	XP82000AAJ10	[Z] DecoTec® 5410	
Print date:	25.04.2023	Revision date: 17.03.2023	EN
Version:	4.0003	Issue date: 17.03.2023	Page 5 / 7

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials** not applicable

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation; Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met.

STOT-single exposure; STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Practical experience/human evidence

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

11.2. Information on other hazards

Endocrine disrupting properties

No information available.

SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Based on available data, the classification criteria are not met.

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.



Page 6/7

Article No.: Print date:	25.04.2023	[Z] DecoTec® 5410 Revision date: 17.03.2023
Version:	4.0003	Issue date: 17.03.2023

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties No information available.

12.7. Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 08 01 11

Appropriate disposal / Package

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number or ID number

not applicable

not applicable

not applicable

- 14.2. UN proper shipping name
- 14.3. Transport hazard class(es)
- 14.4. Packing group

14.5. Environmental hazards

Land transport (ADR/RID)	not applicable
Marine pollutant	not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Further information

Land transport (ADR/RID)

Tunnel restriction code

Sea transport (IMDG)

EmS-No.

not applicable

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according IBC - Code.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU legislation

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive] This product is not classified according to Directive 2012/18/EU.



Page 7/7

Article No.:	XP82000AAJ10	[Z] DecoTec® 5410
Print date:	25.04.2023	Revision date: 17.03.2023
Version:	4.0003	Issue date: 17.03.2023

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]

VOC-value (in g/L) ISO 11890-2: 44 VOC-value (in g/L) ASTM D2369: 166

National regulations

Restrictions of occupation

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Other information:

Switzerland:

Volatile organic compounds (VOC) content in percent by weight: 1

Denmark:

PR-No.:

MAL code (MAL code in mixture):

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous
	Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative
Eurther information	

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.