



Technical Data Sheet

[Z] ZowoSmart® BrushX Plus

Product Description

Product Type

Additive for brushing

- » Modifying agent for brushing application
- » Single-component
- » Easy to use
- » Additive for brushing increases open time, reduces viscosity and improves the brush application of coatings actually designed for spray application

Area of Application

Berger-Zobel top coats

Technical Data

Base of Binder

Acrylate

Color

Whitish

Density

Approx. 1,02 g/ml

Viscosity

Liquid

Processing Instructions

Application Method

- » Stir or shake additive before use
- » 5% [Z] ZowoSmart® BrushX Plus (60g / liter lacquer) added to the amount of top coat
- » In exceptional cases, 10% [Z] ZowoSmart® BrushX Plus can be added
- » Working into the base-coat using a stirrer or shaker as part of the color-homogenization after dosing the pigment pastes.

Processing Viscosity

Ready to use

Processing Conditions

- » Substrate must be dry, clean, load bearing and free of separating substances
- » Moisture content of the wood approx. 13%
- » Approx. 20 °C for substrate, material und environment, ca. 50% relative air humidity
- » Do not process below 15 °C or more than 30 °C
- » Protect freshly painted wood from rain
- » Additive for brushing retards the drying time and the build-up of the block-resistance of the top coat.
- » Drying time depends on applied quantity and ambient conditions. Low temperature and high humidity retard drying. Always ensure adequate temperature and air exchange.

Drying Time

(20 °C / 50% relative Air Humidity)

Cleaning of the tools

Immediately after use with water or [Z] ZowoSmart® HydroCleaner

System Products

Approved top coats with the [Z] ZowoSmart® BrushX Plus

[Z] ZowoTec® 420	[Z] ZowoTec® 421	[Z] ZowoTec® 425	[Z] ZowoTec® 426
[Z] ZowoTec® 444	[Z] ZowoTec® 480	[Z] ZowoTec® 484	[Z] ZowoTec® 485



Technical Data Sheet

Type of Packaging

1 Liter

Additional Information

Special Information

- » Perform a test coating. Check color before use. Subsequent claims cannot be considered. Wood ingredients can cause discoloration!
- » Use only one batch no. per layer and color tone!
- » Please observe ZOBEL steps of coating!

Minimum Shelf Life

15 months cool but free of frost in the closed original packaging.

Safety Instructions

Always read label and product information before use. Please observe the usual precautions during processing and storage. For safety-relevant data and instructions on disposal refer to the Material Safety Data Sheet.

All information provided is state of the art. Because of the large number of options for use and processing, however, obligation and liability must be ruled out. With the appearance of new versions, previous editions lose their validity.