



## Technical Data Sheet

# [Z] ZowoSmart® IsoSprayX

### Product Description

Product Type

Insulating and sealing primer

- » Inhibits effectively the bleeding of wood constituents
- » Can be used in production and on-site repairs
- » Compatible with the [Z] ZowoTec® and [Z] DecoTec® range of products

Area of Application

Types of wood with a high proportion of wood constituents e.g. pine heartwood

### Technical Data

Color

Colorless and white

### Processing Instructions

Application Method

Spray can

If there are discolorations of the coating after coating in the workshop or after installation (e.g. due to excessive building moisture) proceed as follows:

- » Shake the can
- » When reworking on the construction site, lightly sand the affected areas.  
Recommendation: Abrasives of grain size P180 - P240.
- » Paint the discolored areas in thin cross-passes, with sufficient intermediate drying
- » Apply 2 – 3 coats
- » Then coat - without intermediate sanding - with the appropriate Berger-Zobel product

Storage

Always store the can upright

Processing Viscosity

Ready to use

Processing Conditions

- » Substrate must be dry, clean and load bearing
- » Wood moisture approx. 13%
- » Approx. 20 °C for substrate, material und environment, approx. 50% relative air humidity
- » Do not process below 15 °C or more than 30 °C
- » Recoatable after approx. 5 – 10 minutes
- » Drying time depends on applied quantity and ambient conditions. Low temperature and high humidity retard drying. Always ensure adequate temperature and air exchange.

Drying Time

(20 °C / 50% relative air humidity)

Cleaning of the Tools

Immediately after use with [Z] ZowoPlast® 1130 SolvCleaner

### Type of Packaging

400 ml Spray can

### Additional Information

Special Information

- » Perform a test coating. Check color before use. Subsequent claims cannot be considered. Wood ingredients can cause discoloration!
- » Use only one batch no. per layer and color tone!
- » Please observe Berger-Zobel steps of coating!



## Technical Data Sheet

Minimum Shelf Life  
Safety Instructions

12 months cool but free of frost in the closed original packaging

Always read label and product information before use. Please observe the usual precautions during processing and storage. For safety-relevant data and instructions on disposal refer to the Material Safety Data Sheet.

All information provided is state of the art. Because of the large number of options for use and processing, however, obligation and liability must be ruled out. With the appearance of new versions, previous editions lose their validity.